


Diode Schottky



**RoHS
Compliant**



Features:

- Plastic material
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- High current capability, low forward voltage drop.
- High surge capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Guardring for over voltage protection
- High temperature soldering guaranteed: 260°C/10 seconds, 0.25" (6.35mm) from case

Specifications:

Mechanical Data:

Cases	: JEDEC TO-220AB moulded plastic
Terminals	: Pure tin plated, lead free, solderable per MIL-STD-750, Method 2026
Polarity	: As marked
Mounting Position	: Any
Mounting Torque	: 5in. - lbs. Max.
Weight	: 0.08oz, 2.24g

Maximum Ratings and Electrical Characteristics:

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Parameter	Symbol	MBR 3035 CT	MBR 3045 CT	MBR 3050 CT	MBR 3060 CT	MBR 3090 CT	MBR 30100 CT	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	35	45	50	60	90	100	V
Maximum RMS Voltage	V_{RMS}	24	31	35	42	63	70	
Maximum DC Blocking Voltage	V_{DC}	35	45	50	60	90	100	
Maximum Average Forward Rectified Current at $T_C = 130^\circ\text{C}$	$I_{(AV)}$	30						A
Peak Repetitive Forward Current (Rated V_R , Square Wave, 20kHz) at $T_C = 130^\circ\text{C}$	I_{FRM}	30						
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	200						

Diode Schottky





Parameter	Symbol	MBR 3035 CT	MBR 3045 CT	MBR 3050 CT	MBR 3060 CT	MBR 3090 CT	MBR 30100 CT	Units
Peak Repetitive Reverse Surge Current (Note 1)	I_{RRM}	1			0.5			A
Maximum Instantaneous Forward Voltage at: (Note 2) $I_F = 15A, T_C = 25^\circ C$ $I_F = 15A, T_C = 125^\circ C$ $I_F = 30A, T_C = 25^\circ C$ $I_F = 30A, T_C = 125^\circ C$	V_F	0.7 0.6 0.82 0.73		0.77 0.67 - -		0.84 0.7 0.94 0.82		V
Maximum Instantaneous Reverse Current at $T_C = 25^\circ C$ at Rated DC Blocking Voltage at $T_C = 125^\circ C$ (Note 2)	I_R	0.2 15		0.2 10		0.2 7.5		μA μA
Voltage Rate of Change (Rated V_R)	dV/dt	10,000						V/ μS
Typical Junction Capacitance	C_j	600		460		320		pF
Maximum Typical Thermal Resistance, (Note 3)	$R_{\theta JC}$	1				1.5		$^\circ C/W$
Operating Junction Temperature Range	T_J	-65 to +150						$^\circ C$
Storage Temperature Range	T_{STG}	-65 to +175						

Note: 1. 2 μs Pulse Width, $f = 1kHz$.

Note: 2. Pulse Test: 300 μs Pulse Width, 1% Duty Cycle.

Note: 3. Thermal Resistance from Junction to Case Per Leg, with Heatsink Size (4" x 6" x 0.25") Al-Plate.


Ratings and Characteristic Curves (MBR30100CT, 3035CT, 3045CT, 3050CT, 3060CT, 3090CT)




Diode Schottky




Typical Instantaneous Forward Characteristics Per Leg




Typical Reverse Characteristics Per Leg



Typical Junction Capacitance Per Leg




Typical Transient Thermal Characteristics Per Leg



Diode Schottky



TO-220AB



Part Number Table

Description	Part Number
Diode, Schottky, 30A, 100V	MBR30100CT
Diode, Schottky, 30A, 35V	MBR3035CT
Diode, Schottky, 30A, 45V	MBR3045CT
Diode, Schottky, 30A, 50V	MBR3050CT
Diode, Schottky, 30A, 60V	MBR3060CT
Diode, Schottky, 30A, 90V	MBR3090CT

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.